






Datasheet

Fox 2



Notified Body	CE 2756		
Article No., EAN & Weight	EL1AH10	8718657720050	850 grams
	EL1AH10.1.5	8718657720999	900 grams
	EL1AH10.2	8718657720067	950 grams
Standardization	EN354:2010	Lanyards	
Materials used	Line Hooks	Ø 12 mm kernmantle rope (red / black). Steel scaffoldinghook (026 – Brooks). Steel carabiner (223 – Annapurna).	
Description	<div><div></div><div>Work positioning lanyard made of Ø 12 mm kernmantle rope;</div></div> <div><div></div><div>With sewn terminations and protective thimbles;</div></div> <div><div></div><div>Other hooks are available on request;</div></div> <div><div></div><div>Other lengths on request;</div></div> <div><div></div><div>This is no fall protection but work positioning.</div></div>		
Sizes	EL1AH10 EL1AH10.1.5 EL1AH10.2	1 meter 1,5 meter 2 meter	
Break load	> 32 kN		
Packaging	In a bag, manual included.		
Lifetime	Up to 6 years after first use; up to 8 years after production date. Full body harness of a single user, periodically inspected by experts and recorded in inspection log, carefully handled and maintained, stored in accordance with regulations, not in contact with oil, grease or aggressive chemicals, can be used for up to 6 years. Follow the user manual!		