











Datasheet

A2B2E2K2P3 R filter 400, 500 series & T-Air®



| | |
|-----------------------------|---|
| Notified Body | CE 0158 |
| Article number | EF401217 |
| Standardization | EN 14387:2004+A1:2008 Gas filter(s) and combined filter(s) EN148-1 RD40 |
| Particle efficiency: | > 99,98% of particles of 0,3µm at 30 l/min |
| Adsorbent | Activated and impregnated carbon depending per type of filter (A, B, E, K). |
| Description | <ul style="list-style-type: none"> A2: Protects against organic gases & vapors with a boiling point >65°C; Or B2: Inorganic gases and vapours, e.g. chlorine, hydrogen sulphide, hydrogen cyanide; Or E2: Sulphur dioxide, hydrogen chloride; Or K2: Ammonia and organic ammonia derivates; P3: To protect against higher concentrations of harmful dust that can affect the respiratory system. Think of fine dust, highly toxic dust, smoke and mist that can be absorbed into the blood: particles of carcinogenic substances, particles of radioactive substances, bacteria, viruses, enzymes and spores; Aerosol - particles (HEPA); R stands for "Reusable", so can be used multiple times; With EN148-1 (RD40) connection for use on the 300E & 300S half mask; High Capacity Filter; Do not use in closed rooms or rooms with an oxygen content <19%. |
| Materials used | Filter casing: ABS |
| Weight | 408 grams |
| Packaging | Per 2 pieces, purchase per 4 pieces. |
| Note! | Keep an eye on the expiration date for optimal protection. Expiry date is 5 years after date of manufacturing. |