









Datasheet

A2B2P3 R filter 400, 500 series & T-Air®



Notified Body	CE 0158
Article number	EF401215
Standardization	EN 14387:2004+A1:2008 Gas filter(s) and combined filter(s) EN148-1 RD40
Particle efficiency:	> 99,98% of particles of 0,3µm at 30 l/min
Adsorbent	Activated and impregnated carbon depending per type of filter (A, B).
Description	<ul style="list-style-type: none"> A2: Protects against organic gases & vapors with a boiling point >65°C; Or B2: Inorganic gases and vapours, e.g. chlorine, hydrogen sulphide, hydrogen cyanide; P3: To protect against higher concentrations of harmful dust that can affect the respiratory system. Think of fine dust, highly toxic dust, smoke and mist that can be absorbed into the blood: particles of carcinogenic substances, particles of radioactive substances, bacteria, viruses, enzymes and spores; Aerosol - particles (HEPA); R stands for "Reusable", so can be used multiple times; With EN148-1 (RD40) connection for use on the 300E & 300S half mask; High Capacity Filter; Do not use in closed rooms or rooms with an oxygen content <19%.
Materials used	Filter casing: ABS
Weight	402 grams
Packaging	Per 2 pieces, purchase per 4 pieces.
Note!	Keep an eye on the expiration date for optimal protection. Expiry date is 5 years after date of manufacturing.