FITTING INSTRUCTIONS

Ensure hands and earplugs are clean prior to fitting.

Roll earplug with tips of fingers to compact foam into a thin crease-free cylinder.

Insert the compressen earplug well into the ear canal. Pulling the ear outwards and upwards will make fitting easier.

Ensure earplugs are suitably fitted as per diagram.



ATTENUATION TABLE (DECIBELS) NP101 /NP 101C

NPTUT/NPTUTC								
EN352-2:2002								
Frequency(HZ)	63	125	250	500	1000	2000	4000	8000
Mean attenuation(dB)	24,1	29,4	33,9	36,6	35,5	35,8	45,1	45,7
Standart deviation(dB)	4,6	5,2	5,9	6,4	5,9	3,9	3,6	5,7
Mean-minus-standard deviation attenuations(dB)	19,5	24,2	28,0	30,2	29,6	31,9	41,5	40
` '	H=34dB, M	=31dB, L:	=29dB, S	NR=34dB				
NP101 CD								
EN352-2:2002								
Frequency(HZ)	63	125	250	500	1000	2000	4000	8000
Mean attenuation(dB)	27,2	30,2	37,0	42,3	41,7	37,2	47,8	46,1
Standart deviation(dB)	6,1	6,7	4,9	7,1	7,1	5,8	6,3	5,9

NP104 CD

Mean-minus-standard

deviation attenuations(dB)

EN352-2:2002							
Frequency(HZ)	125	250	500	1000	2000	4000	8000
Mean attenuation(dB)	34,5	30,4	36,0	31,9	36,1	41,2	43
Standart deviation(dB)	5,8	4,4	4,7	4,6	4,8	5,6	4,1
Mean-minus-standard deviation attenuations(dB)	28,8	26,0	31,3	27,3	31,2	35,6	38,9

32,1

35.2

34.6

31.4

41.5

40.2

H=32dB, M=29dB, L=28dB, SNR=32dB

23.5

H=34dB, M=34dB, L=31dB, SNR=36dB

WARNING

1. Earplugs should be stored in a cool, dry place away from children's reach.

21,1

- 2. Failure to follow fitting instructions could result in improper fitting of earplugs, which in turn will reduce the effectiveness, and could result in hearing loss & injury.
- 3. These foam earpugs are disposable and not intended for reuse. (except NP104CD)
- 4. Earplug should be removed slowely, by twisting them to slowely break the seal. Removing them to quickly could damage your ear drum.
- 5. Corded earplugs should not be used in a situation where the cord could get aught up during use.
- 6. Keep away from infants and small children. These earplugs are non-toxic, but may interfere with breathing if caught in the trachea. Cords could also become wrapped around the neck, which could lead to serious injury or death.
- 7. Earplugs should be worn at all times in noisy environments.

The EU Declaration of Conformity can be downloaded from our website www.edge-safety.eu by going to the dedicated section of the product.

THE REPORTED ATTENUATION OF THE PROTECTOR WILL ONLY BE OBTAINED IF IT IS GOOD CONDITION AND IS FITTED AS DIRECTED. REFERENCE SHOULD BE MADE TO EN 352-2:2002 TO ENSURE THE CORRECT SELECTION AND USE OF PROTECTORS.



The polybag may present a choking hazard. Keep away from children

C€2777

Notify Body: SATRA Technology Europe Ltd. Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland Notified Body No. 2777

Edge Safety Equipment B.V. Anodeweg 52 4338 RA Middelburg The Netherlands

T. +31 118 745 760 E. <u>sales@edge-safety.eu</u> www.edge-safety.eu

